

# CORROSION RESISTANT SOLENOID VALVE

## IDEAL FOR OUTDOOR & AGGRESSIVE ENVIRONMENTS

Body made of rugged composite material.

All metal parts stainless steel.

NAMUR mount for direct installation on the actuator.

Each port numbered in moulding for easy connections.

## CORROSION PROTECTION FOR ACTUATOR SPRINGS & INTERNAL SURFACES.

In 3/2 form exhaust feed back ensures only clean dry instrument air enters the spring chamber.

## CHOICE OF ELECTRICAL OPERATING VOLTAGES

24V AC/DC, 110 & 220 VAC 50/60 Hz.

Simple & reliable connection via weatherproof DIN connector



## MANUAL OVERRIDE

A red screw provides manual override for operation without an electrical signal.

Turn red screw to 1 & valve will be in the same position as with an energised solenoid.

Turn red screw counter clockwise to 0 to disengage manual override.

## VALVE CAN BE REPURPOSED BY REPOSITIONING PLATE.

### APPLICATIONS

Use 3/2 configuration for spring return actuators

Use 5/2 configuration for double acting actuators



## CONTACT US

[sales@merrimancontrols.com](mailto:sales@merrimancontrols.com)

[www.merrimancontrols.com](http://www.merrimancontrols.com)

Phone 02 43514 022

